NOAA COASTAL MAPPING PROGRAM PROJECT COMPLETION REPORT

PROJECT CA0822

Crescent City, California

Introduction

Coastal Mapping Program (CMP) Project CA0822 provides highly accurate digital shoreline data for Crescent City Harbor and the surrounding shoreline in northern California. The Geographic Cell (GC) may be used in support of the NOAA Nautical Charting Program (NCP) as well as geographic information systems (GIS) for coastal zone management applications.

Project Design

Project CA0822 was designed per a request from the Marine Chart Division (MCD) of the Office of Coast Survey, NOAA for GIS data to update the existing nautical charts for the area.

Field Operations

The field operations consisted of the collection of static and kinematic Global Positioning System (GPS) data and Inertial Measurement Unit (IMU) data and the acquisition of aerial imagery. The photographic mission operations were conducted on May 08th, 2008 with the NOAA Twin Otter aircraft (N48RF). Two strips of natural color digital images were acquired with an approximate ground sample distance of 0.34 meters through the use of an Applanix Digital Sensor System (DSS-439) Single Cam digital camera.

No base station was established for field operations. Airborne kinematic GPS data was collected to determine precise camera positions. Inertial Measurement Unit (IMU) data was collected to determine camera orientations, but could not be used during post processing due to significant errors possibly caused by collection problems.

GPS Data Reduction

GPS data were processed by Remote Sensing Division (RSD) personnel to yield precise camera positions in order to provide a control network necessary for aerotriangulation. Two CORS stations and one UNAVCO station were processed using the NGS Online Processing User Service (OPUS) software to compute fixed baseline solutions for these stations so they could be used as base stations during GPS processing. The airborne kinematic data was processed using Applanix POSPAC (ver. 4.4) software in May 2008.

Aerotriangulation

Routine softcopy aerotriangulation methods were applied to establish a network of precise camera positions and other control for mapping, and to provide model parameters

and orientation elements required for digital compilation. This work was initiated by RSD personnel in June 2010 utilizing a Digital Photogrammetric Workstation (DPW), which is a configuration of computer hardware, modular software components, and other associated peripheral devices. The digital images were measured and adjusted as a single block using BAE Systems SOCET SET (version 5.5.0) photogrammetric suite in conjunction with the Bingo (version 5.6) aerotriangulation software. Upon successful completion of the aerotriangulation process, the Bingo software provided the standard deviations for each aerotriangulated ground point, which were used to compute a predicted horizontal circular error of 0.8 meters based on a 95% confidence level. An Aerotriangulation Report was written and is on file with other project data within the RSD Project Archive.

The project database consists of project parameters and options, camera calibration data, interior orientation parameters, adjusted exterior orientation parameters, and positional listing of all measured points. Positional data is referenced to the North American Datum of 1983 (NAD83).

Compilation

The data compilation phase of this project was initiated by RSD in July 2010. Digital mapping was performed using a DPW in conjunction with the SOCET SET Feature Extraction software module. Feature identification and attribution within the Geographic Cell (GC) were based on image analysis of the digital photographs and information extracted from the appropriate NOAA nautical charts, U.S. Coast Guard Light List and other ancillary sources. Feature attribution was assigned in compliance with the Coastal Cartographic Object Attribute Source Table (C-COAST), which provides the definition and attribution scheme for the full range of cartographic features pertinent to the CMP. Selected features were further modified with additional descriptive information to refine general classification.

Spatial data accuracies for Project CA0822 were determined according to standard Federal Geographic Data Committee (FGDC) practices. Cartographic features were compiled to meet a horizontal accuracy of 1.6 meters at the 95% confidence level. The predicted accuracy of compiled, well defined points is derived by doubling the circular error computed from aerotriangulation statistics.

The following table provides information on the imagery used to complete this project:

Date	Time (UTC)	Roll Number	Photo Numbers	GSD (nominal)	Tide Level*
5-08-08	22:26-22:27	08NC76	16598-16606	0.34 m	1.6
5-08-08	22:33-22:34	08NC76	16608-16617	0.34 m	1.6

^{*} Tide levels are given in meters above MLLW and are based on actual observations recorded by the NOS gauge at Crescent City. The elevation of MHW at Crescent City is 1.9 meters above MLLW.

Final Review

The final review of the project was completed by a senior member of RSD in July of 2010, and included analysis of aerotriangulation results and assessment of the identification and attribution of digital feature data within the GC according to image analysis and criteria defined in C-COAST. The quality control process concluded with an inspection of topological connectivity within the GC using ArcGIS 9.3 software. All project data was evaluated for compliance to CMP requirements.

Comparisons of the largest scale NOAA nautical chart with natural color digital images and compiled project data resulted in the creation of the Chart Evaluation File (CEF). The following nautical chart was used in the comparison process:

18603, Saint George Reef, CA, 1:40,000 scale, 16th edition

End Products and Deliverables

The following specifies the location and identification of the products generated during the completion of this project:

RSD Applications Branch Archive

- Hardcopy of the Airborne Positioning and Orientation Report (APOR)
- Hardcopy of the Aerotriangulation Report
- Hardcopy of the Project Completion Report (PCR)
- Page-size graphic plot of GC10842 file contents, attached to PCR

Remote Sensing Division Electronic Data Library


- Project database
- GC10842 in shapefile format
- Digital copy of the PCR in Adobe PDF format
- CEF in shapefile format

NOAA Shoreline Data Explorer

- GC10842 in shapefile format
- Metadata file for GC10842
- Digital copy of the PCR in Adobe PDF format

End of Report

CRESCENT CITY CALIFORNIA







CA0822

GC10842