NOAA COASTAL MAPPING PROGRAM PROJECT COMPLETION REPORT

PROJECT CT1701-CS-N

Port of New Haven, Connecticut

Introduction

NOAA Coastal Mapping Program (CMP) Project CT1701-CS-N provides highly accurate digital shoreline data for areas of change within the Port of New Haven, Connecticut. The Geographic Cell (GC) may be used in support of the NOAA Nautical Charting Program (NCP) as well as geographic information systems (GIS) for a variety of coastal zone management applications.

Project Design

The design of Project CT1701-CS-N was accomplished by the Requirements Branch (RB) of the Remote Sensing Division (RSD) in response to the need for timely updates to the NOAA chart suite within key U.S. ports. Project requirements were formulated as a result of analysis conducted within the Coast and Shoreline Change Analysis Program (CSCAP), in which NOAA nautical chart products are compared to contemporary high resolution digital imagery in order to ascertain the need for more current shoreline data. A Chart Evaluation File (CEF) was forwarded to the Applications Branch (AB) of RSD once the change analysis was complete. Refer to the CSCAP Memorandum for Project CT1703-CS-T dated June 20, 2017 for details of the chart comparison process.

Field Operations

Field operations for Project CT1701-CS-N consisted of the collection of static and kinematic GPS data and Inertial Measurement Unit (IMU) data, and the acquisition of aerial imagery. Aerial survey operations were conducted in August, 2017 with the NOAA King Air aircraft (N68RF). Three (3) flight lines of natural color (RGB) imagery were acquired using an Applanix DSS dual camera system. Near-infrared (NIR) imagery was also acquired concurrently but was not used. Imagery was acquired at a nominal altitude of 10,500 feet, resulting in an approximate ground sample distance (GSD) of 0.33 meters for the RGB images. Although imagery was not acquired in strict coordination with local tides, the goal was to collect all imagery below the Mean High Water (MHW) tide stage.

GPS Data Reduction

The GPS/IMU data were processed by RSD personnel to yield precise camera positions in order to provide a control network necessary for aerotriangulation (AT). The base station's geodetic position was derived using the NGS Online Processing User Service (OPUS), which computed fixed baseline solutions from nearby CORS stations. The kinematic GPS data was processed using Applanix POSPac MMS (ver. 8.0) software in November 2017. For further information refer to the Airborne Positioning and Orientation Report (APOR) on file with other project data within the RSD Electronic Data Library.

Aerotriangulation

The AT phase of project completion was performed in November 2017. Routine softcopy AT methods were applied to establish a network of precise camera positions and other control for mapping, and to provide model parameters and orientation elements required for digital compilation. The digital images were measured and adjusted as a single block using the Multi-Sensor Triangulation (MST) module of BAE Systems' SOCET SET (ver. 5.6) software on a Windows-based photogrammetric workstation. Upon successful completion of this process, MST provided the standard deviations for each aerotriangulated ground point, which were used to compute a predicted horizontal circular error of 0.3 meters based on a 95% confidence level. An AT Report was written and is on file with other project data within the RSD Electronic Data Library. Positional data is referenced to the North American Datum of 1983 (NAD83).

Compilation

The data compilation phase of this project was accomplished by a member of RSD in December 2017. Digital feature data was compiled using SOCET SET (ver. 5.6) software. Feature identification and attribution within the GC were based on image analysis of the digital photographs and information extracted from the appropriate NOAA nautical charts and other ancillary sources. Feature attribution was assigned in compliance with the Coastal Cartographic Object Attribute Source Table (C-COAST), which provides the definition and attribution scheme for the full range of cartographic features pertinent to the CMP. Selected features were further modified with additional descriptive information to refine general classification.

Spatial data accuracies for Project CT1701-CS-N were determined according to standard Federal Geographic Data Committee (FGDC) practices. Cartographic features were compiled to meet a horizontal accuracy of 0.6 meters at the 95% confidence level. This predicted accuracy of compiled well-defined points is derived by doubling the circular error calculated from the AT statistics.

Date	Time (UTC)	Roll #	Photo #s	Tide Level*
08-16-2017	14:08 - 14:11	17VC49	12281 - 12297	0.9 m
08-16-2017	14:16 - 14:20	17VC49	12298 - 12315	0.8 - 0.9 m
08-16-2017	14:25 - 14:29	17VC49	12316 - 12333	0.8 m

The table below provides information on the imagery used to complete this project:

* Tide levels are given in meters above MLLW and were calculated using the Pydro software tool with a TCARI grid referenced to verified water level observations at NOS gauges. The height of the MHW tidal datum in the project area varies between 1.9 - 2.0 meters above MLLW.

Quality Control / Final Review

The final review of the project was completed by a senior member of RSD in December 2017, and included analysis of AT results and assessment of the identification and attribution of digital feature data within the GC according to image analysis and criteria defined in C-COAST. The quality control process concluded with an inspection of topological connectivity within the GC using ArcGIS (ver. 10.5) software. All project data was evaluated for compliance to CMP requirements.

End Products and Deliverables

The following specifies the location and identification of the products generated during the completion of this project:

Remote Sensing Division Electronic Data Library

- CSCAP evaluation memorandum
- Airborne Positioning and Orientation Report (APOR)
- Aerotriangulation Report
- Project Completion Report (PCR)
- Project database
- GC11367 in shapefile format
- CEF in shapefile format

NOAA Shoreline Data Explorer

- GC11367 in shapefile format
- Metadata file for GC11367
- PCR in Adobe PDF format

End of Report

PORT OF NEW HAVEN

CONNECTICUT

