

NOAA COASTAL MAPPING PROGRAM PROJECT COMPLETION REPORT

PROJECT LA2108-CS-N

Port Fourchon, Louisiana

Introduction

NOAA Coastal Mapping Program (CMP) Project LA2108-CS-N provides highly accurate digital shoreline data for key areas of change for Port Fourchon and vicinity, in Louisiana. The Geographic Cell (GC) may be used in support of the NOAA Nautical Charting Program (NCP) as well as geographic information systems (GIS) for a variety of coastal zone management applications.

Project Design

The design of Project LA2108-CS-N was accomplished by the Requirements Branch (RB) of the Remote Sensing Division (RSD) in response to the need for timely updates to the NOAA chart suite within key U.S. ports. Project requirements were formulated as a result of analysis conducted within the Coast and Shoreline Change Analysis Program (CSCAP), in which NOAA nautical chart products are compared to contemporary high-resolution imagery in order to ascertain the need for more current shoreline data. A Chart Evaluation File (CEF) was forwarded to the Applications Branch (AB) of RSD once the change analysis was completed. Refer to the CSCAP memorandum for Project LA2108-CS-N for details of the chart comparison process.

Field Operations

The field operations consisted of collection of kinematic Global Positioning System (GPS) data and Inertial Measurement Unit (IMU) data, and the acquisition of aerial imagery. Two strips of 4-band digital images (RGB+NIR) utilized for this project were acquired with a NOAA King Air (N68RF) aircraft in September 2022 using an Applanix Digital Sensor System (DSS) aerial camera at a nominal altitude of 10,500 feet, resulting in an approximate ground sample distance (GSD) of 0.23 meters for project imagery. Although imagery was not acquired in strict coordination with local tides, the goal was to collect all imagery below Mean High Water (BMHW).

Direct Georeferencing Data Processing

The GPS/IMU data were processed by RSD personnel to yield precise camera positions and orientations for direct georeferencing (DG) of the imagery. The Airborne kinematic data for project LA2108-CS-N was processed in October 2022 using Applanix POSPac MMS (ver. 8.8) software, utilizing the IN-Fusion PP-RTX processing mode, which is an implementation of Trimble's *CenterPoint RTX* GNSS correction service. For further information refer to the Airborne Positioning and Orientation Report (APOR) on file with other project data within the RSD Electronic Data Library.

The processed GPS/IMU data were used to derive precise exterior orientation (EO) values of the digital aerial imagery camera centers required for digital feature extraction. The predicted

horizontal accuracy of the imagery was calculated using an Exterior Orientation Total Propagated Uncertainty (EO-TPU) tool developed by NGS. Using this tool, the predicted horizontal uncertainty at the 95% confidence level was calculated to be 0.57 meters. Stereo-models were examined in order to verify the quality of the DG data and ensure acceptable levels of parallax for mapping purposes.

Compilation

Data compilation was accomplished by a member of AB in March 2023. Digital feature data was compiled in stereo from the RGB imagery using Esri's ArcGIS Pro software (ver. 3.1.0). Feature identification and attribution within the GC were based on image analysis of the aerial imagery and information extracted from the largest scale NOAA Electronic Navigational Charts (ENCs) and other ancillary sources. Feature attribution was assigned in compliance with the Coastal Cartographic Object Attribute Source Table (C-COAST), which provides the definition and attribution scheme for the full range of cartographic features pertinent to the CMP. Selected features were further modified with additional descriptive information to refine general classification.

Spatial data accuracies for Project LA2108-CS-N were determined according to standard Federal Geographic Data Committee (FGDC) practices. Cartographic features were compiled to meet a horizontal accuracy of 1.1 meters at the 95% confidence level. This predicted accuracy of compiled well-defined points is derived by doubling the imagery accuracy computed from the EO-TPU tool.

The following table provides information on the images used in the project completion:

Date	Time (UTC)	Flight Line / Images	Water Level*
14-SEP-2022	16:38 – 16:39	61-002 / 055965 – 055968	0.3 m
14-SEP-2022	16:39 – 16:40	61-002 / 055971 – 055978	0.3 m
14-SEP-2022	17:08 – 17:11	61-001 / 055983 – 055996	0.3 m
14-SEP-2022	17:17 – 17:18	61-002 / 056001 – 056002	0.3 m

* Tide levels are given in meters above MLLW datum and were calculated using the Pydro software tool with a TCARI grid referenced to verified water level observations from various NOS gauges in the vicinity of the project. The height of the MHW tidal datum is 0.364 meters above MLLW at the Port Fourchon, LA gauge (8762075).

Quality Control / Final Review

The final review of the project was completed by senior CMP personnel in March 2023, and included analysis of DG results and assessment of the identification and attribution of digital feature data within the GC according to image analysis and criteria defined in C-COAST. The quality control process concluded with an inspection of topological connectivity within the GC using Esri's ArcGIS (ver. 10.8.2) software. All project data was evaluated for compliance to CMP requirements.

End Products and Deliverables

The following specifies the location and identification of end products generated during the completion of this project:

Remote Sensing Division Electronic Data Library

- CSCAP evaluation memorandum
- Airborne Positioning and Orientation Report (APOR)
- Project database
- Project Completion Report (PCR)
- GC11923 in shapefile format
- CEF in shapefile format


NOAA Shoreline Data Explorer

- GC11923 in shapefile format
- Metadata file for GC11923
- PCR in Adobe PDF format

End of Report

PORT FOURCHON

LOUISIANA



Overview



LA2108-CS-N

GC11923