

NOAA COASTAL MAPPING PROGRAM PROJECT COMPLETION REPORT

PROJECT NY0801

Port of Albany, New York

Introduction

Coastal Mapping Program (CMP) Project NY0801 provides highly accurate digital shoreline data for the Hudson River from Albany to Paarda Hook, New York. The Geographic Cell (GC) may be used in support of the NOAA Nautical Charting Program (NCP) as well as geographic information systems (GIS) for a variety of coastal zone management applications.

Project Design

The design of Project NY0801 was accomplished by the Requirements Branch (RB) of the Remote Sensing Division (RSD). RB formulated the photographic mission instructions for this project following the guidelines of the Photo Mission Standard Operating Procedure. The instructions discussed the project's purpose, geographic area of coverage, scope and priority; photographic requirements; flight line priority; Global Positioning System (GPS) data collection procedures and guidelines for both kinematic and static surveys; data recording and handling instructions; and contact and communication information. RB created a Project Layout Diagram, flight maps and input files for the aircraft's flight management system.

Field Operations

The field operations consisted of the collection of static and kinematic Global Positioning System (GPS) data and Inertial Measurement Unit (IMU) data and the acquisition of aerial imagery. The photographic mission operations were conducted on May 25, 2008 with the NOAA Cessna Citation II (N52RF) aircraft. Two strips of RGB (color) digital images were acquired with an Applanix Digital Sensor System (DSS) 439 aerial camera at a nominal altitude of 10,000 feet, resulting in an approximate ground sample distance (GSD) of 0.35 meters.

GPS Data Reduction

The GPS/IMU data were processed by RSD personnel to yield precise camera positions in order to provide a control network necessary for aerotriangulation (AT). The base station's geodetic position was derived using the NGS Online Processing User Service (OPUS), which computed fixed baseline solutions from nearby CORS stations. The kinematic GPS data was processed using POSPac MMS 6.1.0 GPS/IMU software in January 2014. For further information refer to the Airborne Positioning and Orientation Reports (APOR) on file with other project data within the RSD Project Archive.

Aerotriangulation

Routine softcopy AT methods were applied to establish a network of precise camera positions and other control for mapping, and to provide model parameters and orientation elements required for digital compilation. This work was performed by RSD personnel in February 2014.

utilizing a Digital Photogrammetric Workstation (DPW), which is a configuration of computer hardware, modular software components, and other associated peripheral devices. The digital images were measured and adjusted as a single block using the SOCET GXP (ver. 4.1.0) suite of digital photogrammetric software. The Triangulation module of SOCET GXP was used to perform point measurements and an AT adjustment, and evaluate the accuracy of the adjustment. Upon successful completion of this process, the triangulation software provided the standard deviations for each aerotriangulated ground point, which were used to compute a predicted horizontal circular error of 0.6 meters based on a 95% confidence level. An AT report was written and is on file with other project data within the RSD Project Archive. Positional data is referenced to the North American Datum of 1983 (NAD83).

Compilation

The data compilation phase of this project was accomplished by a member of AB in March 2014. Digital feature data was compiled using SOCET GXP (v4.1.0) software. Feature attribution was assigned in compliance with the Coastal Cartographic Object Attribute Source Table (C-COAST), which provides the definition and attribution scheme for the full range of cartographic features pertinent to the CMP.

Spatial data accuracies for Project NY0801 were determined according to standard Federal Geographic Data Committee (FGDC) practices. Cartographic features were compiled to meet a horizontal accuracy of 1.1 meters at the 95% confidence level. This predicted accuracy of compiled well-defined points is derived by doubling the circular error calculated from the AT statistics.

The following table provides information on the imagery used to complete this project:

Date	Time (UTC)	Roll #	Photo #s	~GSD	Tide Level*
05-25-08	15:14 – 15:17	08NC10	2446 – 2464	0.35 m	1.4 – 1.2 m
05-25-08	15:22 – 15:24	08NC10	2465 – 2481	0.35 m	1.2 – 1.3 m

* Tide levels are given in meters above MLLW based on predicted water levels at the time of photography for the Albany and Castleton NOS tide stations. The elevation of the MHW tidal datum in the project area 1.6 meters above MLLW.

Quality Control / Final Review

Final review of the project was completed by a senior member of RSD in March 2014, and included analysis of AT results and assessment of the identification and attribution of digital feature data within the GC according to image analysis and criteria defined in C-COAST. The quality control process concluded with an inspection of topological connectivity within the GC using ArcGIS 10.1 software. All project data was evaluated for compliance to CMP requirements.

Comparisons of the largest scale NOAA nautical charts with natural color images and compiled project data resulted in creation of the Chart Evaluation File (CEF). The following nautical chart was used in the comparison process:

12348, Hudson River, Coxsackie to Troy, NY, 1:40,000 scale, 34th Ed., Jun. /10

End Products and Deliverables

The following specifies the location and identification of end products generated during the completion of this project:

RSD Applications Branch Archive

- Hardcopy of the Airborne Positioning and Orientation Report (APOR)
- Hardcopy of the Aerotriangulation Report
- Hardcopy of the Project Completion Report (PCR)
- Page size graphic plot of GC11054 file contents, attached to PCR

Remote Sensing Division Electronic Data Library

- Project database
- GC11054 in shapefile format
- Digital copy of the PCR in Adobe PDF format
- CEF in shapefile format


NOAA Shoreline Data Explorer

- GC11054 in shapefile format
- Metadata file for GC11054
- Digital copy of the PCR in Adobe PDF format


End of Report

PORT OF ALBANY

NEW YORK



Overview



NY0801

GC11054