### 9195

の け い び

Diag. Cht. No. 1286-2
Form 504
U. S. COAST AND GEODETIC SURVEY
DEPARTMENT OF COMMERCE
DESCRIPTIVE REPORT
Type of Survey TOPOGRAPHIC
Field No. Ph-36(48)C Office No. T-9195
LOCALITY
State TEXAS
General locality KENEDY & KLEBERG COUNTIES
Locality RIVIERA BEACH
1948-52
CHIEF OF PARTY G.E.Morris, Jr., Chief of Field Party. H.A.Paton, Baltimore Photogrammetric Office
LIBRARY & ARCHIVES
DATE

### DATA RECORD

T - 9195

Project No. (II):

Quadrangle Name (IV):

Riviera Beach, SW.

PH-36(48)C

Field Office (II): Brownsville, Texas

Chief of Party: George E. Morris, Jr.

Photogrammetric Office (III):Baltimore, Maryland.

Officer-in-Charge: Hubert A. Paton

Instructions dated (II) (III): 14 February 1949

Copy filed in Division of

8 June 1949

Photogrammetry (IV)

26 July 1949) Supplement No. 2 28 July 1949)

Office Files

24 Feb. 1950 - Supplement No. 1

Method of Compilation (III): Graphic

Manuscript Scale (III): 1:20,000

Stereoscopic Plotting Instrument Scale (III):

Scale Factor (III): 1.000

Date received in Washington Office (IV): 17 Oct '50 Date reported to Nautical Chart Branch (IV): 20 Oct - 50

Applied to Chart No. 1117

Date: Nov 1951

Date registered (IV): 10-7-52

Publication Scale (IV):

Publication date (IV):

Geographic Datum (III):

N. A. 1927

Vertical Datum (III):

Mean sea level except as follows: Elevations shown as (25) refer to mean high water Elevations shown as  $(\underline{\delta})$  refer to sounding datum i.e., mean low water or mean lower low water

Reference Station (III): Robbins, Ecc., 1931

Lat.: 27° 18' 22.778" (701.lm)

Long.: 97° 44' 20.286" (557.8m)

Adjusted XXXXXXXXXX

Plane Coordinates (IV):


State: Texas

Zone: South

Roman numerals indicate whether the item is to be entered by (II) Field Party, (III) Photogrammetric Office,

When entering names of personnel on this record give the surname and initials, not initials only.

M-2618-12(4)



Areas contoured by various personnel (Show name within area) (II) (III)

### DATA RECORD

Field Inspection by (II): G. B. Torbert

Date: August, September

and October 1949

Planetable contouring by (iI): G. B. Torbert

Date: August, September

and October 1949

Completion Surveys by (II): W. H. Sheatouse

Date: 2-14-52

Mean High Water Location (III) (State date and method of location): 12-9-48 ) dates of photographs 12-10-48 )

and June to September 1949, date of field inspection

Projection and Grids ruled by (IV): W. E. W.

Date: 10-19-49

Projection and Grids checked by (IV): H. D. W.

Date: 10-21-49

Control plotted by (III): F. J. Tarcza

Date: 1-3-50

Control checked by (III): W. L. Lineweaver

Date: 1-3-50

Radial Plot and Service Complete

EXAMPLE TO Tarcza

Date:

Date:

1-18-50

Planimetry

Contours

Stereoscopic Instrument compilation (III):

Date:

Manuscript delineated by (III): B. Kurs

Date: 10-3-50

Photogrammetric Office Review by (III): R. Glaser

ate: 10-10-50

Elevations on Manuscript R. Glaser

Date: 10

10-10-50

checked by (II) (III):

Form T-Page 3

M-2618-12(4)

### Camera (kind or source) (IIII.S.C.G.S. Type "O" single lens camera, focal length 6"

		PHOTOGRAPHS (III)		
Number	Date	Time	Scale	Stage of Tide
48-0-2129 to 48-0-2132 incl	12-10-48	1107	1:20,000	Not computed
48-0-2164 to 48-0-2167 incl	12-10-48	1138	1:20,000	(negligible)
48-0-1704 48- <b>0-</b> 1705 48-0-1707	-12-9-48 12-9-48 12-9-48	1209 1210 1210	1 <sup>2</sup> 20,000 1:20,000 1:20,000	·

### Tide (III)

Reference Station: Galveston, Texas

Subordinate Station: The mean tange of tide 15 less

Subordinate Station: +hm 1/2 Foot.

Washington Office Review by (IV): G. B. Willey

Date: 23 May 1952

Range | Range

|Ratio of | Mean | Spring

Ranges

1:0

Final Drafting by (IV):

Date:

Drafting verified for reproduction by (IV):

Date:

Proof Edit by (IV):

Date:

Land Area (Sq. Statute Miles) (III): 39

Shoreline (More than 200 meters to opposite shore) (III): 36
Shoreline (Less than 200 meters to opposite shore) (III): 3

Control Leveling - Miles (II): 30.7

Number of Triangulation Stations searched for (II): 11 Recovered: 5 Identified: 5
Number of BMs searched for (II): 26 Recovered: 22 Identified: 14


Number of Recoverable Photo Stations established (III): 15
Number of Temporary Photo Hydro Stations established (III):

Remarks: STATISTICS OUTSIDE THE QUADRANGLE (ALSO PROJECT):

- (1) 3 USC&GS triangulation stations were searched for, 1 was recovered, and 1 was identified.
- (2) 9 USC&GS first and second-order bench marks were searched for, and 8 were recovered.

Form T-Page 4

M-2618-12(4)



Project Ph-36(4d) consists of fifty-two quadrangles at 1:20,000, each 7.5 minuted in latitude and longitude, covering the Gulf Coast of Texas and the Intraceastal Unterway from Araness Bay to Brownsville and the Herican Berder. Adjoining the project to the north is a ceries of shoveline surveys in Part IV of Froject Ph-14(46).

Information concerning Th-36(48) in its breader appears will be included in a project completion report to be compiled at the conclusion of the review of all surveys in this project.

Twenty-six of the queleungles in this project are topographic surveys and are to be published at 1:24,000 seels by the feelegical survey. The other twenty-six quadrangles are planimetric surveys. Of these, nineteen are to be used as based by the feelegical survey for the compilation of 7.5 minute topographic quadrangles and will not be published as planimetric maps. The remaining seven, T-9175, T-9176, T-9177, T-9181, T-9169, T-9204, and T-9206, will be published as planimetric maps.

Cloth-backed liths graphic prints of the original may manuscripts at compilation scale and the descriptive reports for all maps in this project will be filed in the Europe Archives. Cloth-backed copies of the published topographic quetrangles at 1825,000 scale will also be filed.

All special reports except the Goog. Names Report will be filed in the Project Completion Report.

### 2. AREAL FIELD INSPECTION

This quadrangle is situated at the head of Baffin Bay where Grullo Bayou and Laguna Salado meet to form the bay. Approximately 80 per cent of the quadrangle is land area. The quadrangle lies in two counties, Kenedy, and Kleberg, that are separated by Laguna Salado and Baffin Bay.

About 24 square miles of land area, at the head of Baffin Bay, west of Grullo Bayou and north of Laguna Salado, has been developed as diversified farmland, is moderately populated, and is served by an adequate road net. Several small cabin, fishing, and pleasure boats are based out of Loyola Beach and Riviera Beach. The relief in this area varies from prominent to relatively flat near the water areas, and the entire area is thickly interspersed with intermittent ponds.

The remaining land area is all in the King and Kenedy Ranches, is unpopulated, and is accessible only by unimproved roads through locked gates. The area south of Laguna Salado and Baffin Bay is owned by the Kenedy Ranch, and the area east of Grullo Bayou and north of Baffin Bay is owned by the King Ranch. Both ranch areas are used exclusively for cattle grazing, and, because of an absence of cultural features; fences, windmills, flowing wells, and corrals have been indicated on the field inspection photographs. The relief is relatively flat with an occasional prominent knoll.

Photography was adequate and no vegetation growths peculiar to the general area were encountered.

Field inspection was performed on the following photographs: 48-0-1705, 48-0-1707, 48-0-2129, 48-0-2130, 48-0-2131(1 of 2), 48-0-2131(2 of 2), 48-0-2132, 48-0-2164, 48-0-2165, 48-0-2166, 48-0-2167.

### 3. HORIZONTAL CONTROL

No original descriptions were available to assist in the recovery of "BUENA VISTA HOTEL SOUTH CHIMNEY 1912" and "BUENA VISTA HOTEL NORTH CHIMNEY 1912", at Riviera Beach. However, a thorough investigation was made, as evidenced by the recovery notes, and the south chimney is believed to be still standing and was identified. Since there is a chance that the identified chimney might not be the point observed in 1912 the following statement was added to the recovery note for BUENA VISTA HOTEL SOUTH CHIMNEY 1912, "More positive recovery will depend on the radial plot for quadrangle T-9195() in Project Ph-36(48).

The forgoing note was also added to the recovery note for BUENA VISTA HOTEL WATER TANK 1939" since if was impossible to reconcile the original description with local information.

Horizontal control identification was performed on the following photographs: 48-0-1705, 48-0-2129, 48-0-2165, 48-0-2167, 48-0-2185.

### 4. VERTICAL CONTROL

Within the quadrangle, the following second-order USC&GS bench marks were recovered and identified, approximately, on the contour photographs: D 635 RESET, E 635, F 635 RESET, G 635 RESET, H 635 RESET, J 635, K 635, L 635, P 635, Q 635, R 635, U 918, ROBBINS RM 1, ROBBINS RM 2.

USC&GS second-order bench mark M 635 and N 635, within the quadrangle, were found broken off and the disks were removed by this party.

To provide additional control for contours, 30.7 miles of 4th-order levels were run between the bench marks within the project limits, between level points 95-1 to 95-30. All closures were under .20 foot except one 6.4 mile loop with a closure of .70 foot. The .70 foot was prorated throughout the loop.

Level points were spotted on the contour photographs.

### 5. CONTOURS AND DRAINAGE

Contouring was done by standard planetable methods on the single lens ratio prints. Photographs were carefully examined under the field stereoscope prior to field work and again prior to inking of the pencil contours. Moderate relief, large open areas, and the use of vehicles by the rodmen greatly facilitated the field contouring on the King and Kenedy Ranches.

Vertical accuracy checks run as a check on the topographer have been indicated in violet ink and required changes in the contours also indicated in violet ink. Original contours in brown ink that were found in error have been deleted with green "X's".

Satisfactory contour junctions were made with quadrangle T-9191( ) on the north, quadrangle T-9196( ) on the east, and T-9199( ) on the south. A planetable traverse was run along the project limit on the west side of the quadrangle.

Contouring was done on the following photographs: 48-0-2129, 48-0-2130, 48-0-2131(1 of 2), 48-0-2132, 48-0-2164, 48-0-2165, 48-0-2166, 48-0-2167.

All drainage upstream of the mean water line is intermittent.

### 6. WOODLAND COVER

Woodland cover consists principally of scrub growths of mesquite which covers about 20 per cent of the quadrangle. The mesquite ranges in height up to twenty feet, and all areas above six feet covering more than 30 per cent of the ground area have been classified "T".

### 7. SHORELINE AND SHORELINE FEATURES

There is no periodic tide in the quadrangle.

The exact elevation of the mean water line in Laguna Salado, Grullo Bayou, and Baffin Bay is not known. Tide gage information from a private source will be made available early in 1950. See "Special Report on the Identification and Delineation of Shoreline in the Laguna Madre, Project Ph-36(48)" to be submitted at a later date.

Most of the delineated mean water line is along a definite bank (tone change) and a change of a few tenths of a foot in elevation of the EWL will not materially displace this line horizontally.

In other areas the mean water line was located by planetable at 0.4 ft, elevation and the elevations are inked along this delineated MWL. This 0.4 ft. elevation was selected after a thorough investigation of the area, and considerable discussion with oil company officials and local inhabitants interested in the elevation of the MWL.

If the special report furnishes a different elevation of the mean water line it will be necessary to relocate the MWL only along the east shore of Grullo Bayou on photograph 48-0-2131(1 of 2) and 48-0-2132, and for about 1/2 mile along the west shore just south of the north quadrangle limit on photograph 48-0-2164.

The bulk of the storm water line is along a prominent bluff and very close to the MWL. Where no prominent bluff exists, the line is along the vegetation line, or five-foot contour, whichever is found farther offshore.

Shoreline inspection has been shown on the following photographs: 48-0-1704, 48-0-1705, 48-0-1707, 48-0-2129, 48-0-2130, 48-0-2131(1 of 2)(2 of 2), 48-0-2132, 48-0-2164, 48-0-2166, 48-0-2167.

### 8. OFFSHORE FEATURES

There were no offshore features to be investigated by the field inspector.

### 9. LANDMARKS AND AIDS

Chart Letter 268 (50)

Three landmarks, west of present chart limits, are submitted on Form 567. Two are triangulation, and the other was pricked direct and is described on Form 524 that is submitted with field records for this quadrangle. Landmark characteristics are also inked on the photographs used for identification.

There are no nautical or aeronautical aids within the quadrangle.

### 10. BOUNDARIES, MONUMENTS, AND LINES

For that part of the quadrangle north of Laguna Salado and Baffin Bay, see "Special Report, Boundaries, Baffin Bay to Latitude 28 00', Project Ph-36(48)".

For the remainder of the quadrangle, see "Special Report, Boundaries, Baffin Bay to the Rio Grande, Project Ph-36(48)".

### 11. OTHER CONTROL

In addition to the landmark described on Form 524 (Par.9), 14 monumented topographic stations were established.

Identification was performed on the following photographs: 48-0-1704, 48-0-1705, 48-0-1707, 48-0-2129, 48-0-2130, 48-0-2131(2 of 2), 48-0-2132, 48-0-2164, 48-0-2166.

### 12. OTHER INTERIOR FEATURES

All roads were classified in accordance with Photogrammetry Instructions No. 10 dated 14 April 1947, and amendment dated 24 October 1949, and the Topographic Manual.

There are no bridges or cables over navigable waters within the area.

All buildings to be shown have been classified in accordance with Photogrammetry Instructions No. 29 dated 1 October 1948, and the Topographic Manual.

One Navy auxiliary landing field, Field 55, is within the quadrangle and has been indicated on photograph 48-0-2166. The field is seldom used for flying purposes but is actively used as a bombing range by training planes based at the Naval Air Station in Corpus Christi, Texas.

### 13. GEOGRAPHIC NAMES

For that part of the quadrangle north of Laguna Salado and Baffin Bay, see "Special Report, Geographic Names, Aransas Bay to Baffin Bay, Project Ph-36(48)".

For the remainder of the rquad., see "Special Report, Geographic Names, Baffin Bay to Port Mansfield (Red Fish Landing), Project Ph-36(48".

### 14. SPECIAL REPORTS AND SUPPLEMENTAL DATA

"Special Report, Boundaries, Baffin Bay to Latitude 28000', Project Ph-36(48)", forwarded to Washington 20 July 1949.

"Special Report, Boundaries, Baffin Bay to the Rio Grande, Project Ph-36(48)", to be submitted to Washington at a later date.

"Special Report, Geographic Names, Aransas Bay to Baffin Bay, Project Ph-36(48)", forwarded to Washington 27 July 1949.

"Special Report, Geographic Names, Baffin Bay to Port Mansfield (Red Fish Landing), Project Ph-36(48)", to be submitted to Washington at a later date.

"Special Report on the Identification and Delineation of Shoreline in the Laguna Madre, Project Ph-36(48)", to be submitted to Washington at a later date.

Records, Quadrangle T-9195( ), to Baltimore 10 November 1949 by letter of transmittal Ph-36 Field 44 .

Submitted 4 November 1949

Surey B. Intest.
Grover B. Torbert
Cartographic Survey Aid

Approved 10 November 1949

George E. Morris, Jr.
Chief of Party

										Photogrammetry
MAP T. 9195		PROJE	CT NO.	-h-	PROJECT NO. Ph-36(48)C	SCALE OF MAP 1:20,000	20,000	SC	SCALE FACTOR	OR None
STATION	SOURCE OF INFORMATION (INDEX)	DATUM	LATITUE	DE OR y-	LATITUDE OR y-COORDINATE LONGITUDE OR x-COORDINATE	DISTANCE FROM GRID IN FEET. OR PROJECTION LINE IN METERS FORWARD (BACK)	DATUM		N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)	FACTOR DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)
BUENA VISTA HOTEL WATER TANK, 1939	L G-4197 P. 123	N.A. 1927	27	77 7	24.67			758.3	1087.4	
RITEMA VICTA HOTEL	G_ 6830				-			19.5	1630.5	
		=		33	59.84			757.7	1289.0	
GERMAN CATHOLIC 1913	GEZ-G-		27		01.92			59.1	1787.6	
CHURCH STEEPLE, 1931	1 755 to	=	26	44	58.34			1603.8	45.6	
PASADISO, 1912	755 755	:	27	15	38,122			1173.4	673.4	
	P. 39	=	26	38	31.637		-	870.2	780.2	
SUB.PT. PASADISO,			27	15				1109.8	737.0	
77.7			26	38				866.9	783.5	
ROBBINS, ECC.,	GEZ-G-755		27	18	22.778			701.1	1145.6	
1771	P.39	=	26	7 77	20,286			557.8	1092,0	
SUB.PT. ROBBINS, =			27	18				734.0	1112.7	
ECC., 1931			26	44				356.5	1293,3	
Catholic Church Spire,	Texas the	:		20	01.917			59.0	1788.0	
1913	_		26	4	58.343			1603.8	45.6	•
	77.41		8							
						3				
,800										
1 FT.=.3048006 METER DEWEAVER COMPUTED BY: G. G. WILLEY	leaver ley	DATE.		ecemb	27 December 1949	F.J. Tarcza	ırcza		Dec.30,	M.2388.12
										***************************************

### COMPILATION REPORT

### T-9195

### PHOTOGRAMMETRIC PLOT REPORT

The photogrammetric plot report covering this survey was submitted 3 May 1950 with the descriptive report for Survey No. T-9191.

### 31. DELINEATION

Delineation was by graphic methods. Photo coverage and field inspection were satisfactory. A discrepancy overlay is being submitted with the manuscript.

### 32. CONTROL

The identification, density and placement of horizontal control was adequate.

Subsequent to the completion of the radial plot for this area, a checked geographic position for OUR LADY OF CONSOLATION CATH. CH. SP.,1949 was received. This station is the same as GERMAN CATH. CH. STEEPLE, 1931, for which there was a "no check" position and for which a radially plotted position was established when the station could not be held. The checked geographic position proved that the unchecked position was not in error as stated in the radial plot report. No attempt was made to change the plot as the radially plotted position falls about 0.3mm from the geographic position.

### 33. SUPPLEMENTAL DATA

- 1. Plan of outlying Field 55, U. S. Naval Air Station, Corpus Christi, Texas. The military reservation boundary was taken from this plan.
- 2. General land office map of Kleberg County Boundary Sheet No.2. Used for precinct and county boundaries.
- 3. Geographic names standard No. 9 dated 11-4-49 on the Corps of Engineers, Sarita quadrangle.
  - 4. Wye Leveling data for T-9195 (one vol.)

### 34. CONTOURS AND DRAINAGE

No comment.

### 35. SHORELINE AND ALONGSHORE FEATURES

Field inspection of the mean water line and storm water line was adequate. (Refer to the field inspection report, item No. 7).

The field inspected storm water line was used as the approximate limits of intermittently flooded areas.

There were no low water or shoal lines delineated on the manuscript.

### 36. OFFSHORE DETAILS

No comment

### 37. LANDMARKS AND AIDS

Three landmarks for charts fall within this survey. Form 567 for these landmarks is being submitted with this report.

### 38. CONTROL FOR FUTURE SURVEYS

Forms 524 for fifteen recoverable topographic stations were prepared by the field party and completed in the compilation office. These forms will be submitted with this report.

A list of the recoverable topographic stations will be found in item No. 49.

### 39. JUNCTIONS

Junctions have been satisfactorily completed with T-9191 to the north, T-9196 to the east, and with T-9199 to the south. To the west is the project limits .

### 40. HORIZONTAL AND VERTICAL ACCURACY

No comment.

### 41. LANDING FIELDS

Navy auxiliary landing field No. 55 in the southwest section of the quadrangle, is now closed. (See field report, item 12).

### 42 through 45.

Inapplicable.

### 46. COMPARISON WITH EXISTING MAPS

Comparison was made with the Corps of Engineers, Sarita quadrangle scale 1:125,000, edition of 1920, revised 1928.

The south shore of the Laguna Salada just south of Riviera Beach has built up considerably since the above survey.

### 47. COMPARISON WITH NAUTICAL CHARTS

The area of this survey is not covered by any large scale Harbor or Coast charts. The area can be found only on General Chart No. 1117, scale 1:460,732 and on Sailing Chart No. 1007, scale 1:2,161,530.

Respectfully submitted

10 October 1950

Raymond Glaser

Cartographic and Surveying Aid

Approved and forwarded 17 October 1950

Hubert A. Paton Comdr., USC&GS

Officer in Charge

### 48. GEOGRAPHIC NAMES

Except where another source of information is indicated, the following names were taken from geographic names standard No. 9 (11-4-49) and another unnumbered geographic names sheet:

Baffin Bay School

(not shown on manuscript; according to field inspection this school was moved to Riviera 24 October 1949. It is not known if the building remains)

Cayo Tel Grullo (recent B. G. M. decision) Chalio Well

Commissioner Precinct 3) from boundary data Commissioner Precinct 4) omitted from manu-

seript - leastion in doubt.

grum Point

Kenedy Ranch ) from field report King Ranch

Kleberg County) from boundary data

Kenedy County )

Laguna De Zos Olmos Laguna Salada

La Parra Landing Loyola Beach

Consolation

Our Lady of Consation Church ) comitted from Our Lady of Consation School ) manuscript for verification of spelling.

Radicha Creek Riviera Beach

Piede Gallo (in original names

Sandy Hook (Omitted from manuscriptlocation in doubt)

Vattman Creek Visnaga Windmill

Road No 628

Road No. 771

Las Puertas Artesian Well

Names underlined in red are approved. 5-1-51. L. HECK 5-21-52 Q.2.W.

### 49. NOTES FOR THE HYDROGRAPHER

The following is a list of recoverable topographic stations shown on the manuscript:

ALSO, 1949 BARN, 1949 BOOT, 1949

BULL, 1948, 1949

CANE, 1949 CARL, 1949

DEBT, 1949

ECHO, 1949

HARP, 1949

HORN ,1949

ITEM, 1949

STAN, 1949

s 567-3, 1949

S 567-11, 1949

WINE, 1949

### PHOTOGRAMMETRIC OFFICE REVIEW

T. 9155

1. Projection and grids2. Title3. Ma	nuscript numbers 4 4. Manuscript size 4
CONTROL  5. Horizontal control stations of third-order or higher accurate than third-order accuracy (topographic stations)  9. Plotting of sextant fixes	racy 2 6. Recoverable horizontal stations of less
	DRE AREAS Chart Data)
12. Shoreline 13 Low water line 14- R to navigation 17. Landmarks 18. Other shore cultural features	
PHYSICAL  20. Water features 21. Natural ground cover  Instrument contours 24. Contours in general  features	FEATURES  22. Planetable contours  23. Stereoscopi  25. Spot elevations  26. Other physics
CULTURAL 27. Roads 28. Buildings 29 <del>- Reilroad</del>	
BOUNG 31. Boundary lines 32- Rublic-land lines	DARIES
MISCELL 33. Geographic names 2 34. Junctions 2 3 overlay 37. Descriptive Report 2 38. Fie 40. Laymond Marks Reviewer	ANFOLIS
	CORRECTIONS TO THE MANUSCRIPT
42. Additions and corrections furnished by the field comp manuscript is now complete except as noted under item 4	
Compiler	Supervisor

Field Edit Report, T-9195

51. <u>Methods</u>.--All roads were ridden out to check their classification, verify cultural and natural features and answer questions asked by the reviewer. All shoreline was ridden or walked over and carefully checked. Where the low-water line was in question it was investigated at low tide. Additions to the map were made by tape or standard planetable methods.

Deletions, additions and corrections have been made on the Field Edit Sheets (numbered 1 and 2), Discrepancy Print and photographs 48-0-2129, 2131, 2132, 2164, 2165 and 2166.

Violet ink was used for corrections and additions; green for deletions. A legend is shown on Field Edit Sheet No. 2.

- 52. Adequacy of compilation -- Compilation of map details is adequate and will be complete after application of field edit information.
- 53. <u>Map accuracy</u>.--Horizontal accuracy was checked by planetable method in connection with testing of contours and location of new roads. Delineated points, such as road intersections, were used to take off from and tie into. From this method and visual inspection, the horizontal accuracy appears good.

One vertical accuracy test was made. It is located at latitude 27 degrees 19 minutes, longitude 97 degrees 45 minutes. Horizontally it began at point "A" (road intersection) and closures were made at point "B" (\( \Delta \) Robbins Ecc., 1931) and point "C" (road intersection). Vertical origin was at bench mark Robbins Ecc. R. M. 2 and termination was at bench mark F 635. The horizontal error of closure was 60 feet (1.0mm) short and the vertical error of closure was 0.5 foot high. No adjustments were made.

The results are as follows:

- 51 points tested.
- 49 points in error less than \( \frac{1}{2} \) contour interval.
- 2 points found in error more than } contour interval.
- O points found in error more than 5 feet.
- 96% of all points tested were within the allowable limits of accuracy.

The necessary corrections to contours were made on Field Edit Sheet No. 1. In general the pattern of the contours is good and appears to be well within the required accuracy.

54. Recommendations .-- None offered.

- 55. Examination of proof copy. -- It is recommended that proof copies of the map be sent to the following people for examination. --
- 11) King Ranch Office, attention Mr. Robert G. Wells, Kingsville, Texas, for the King Ranch part.
- (2) Mr. Charles G. Patterson, County Surveyor, Kingsville, Texas, for the part west of the Cayo del Grullo and north of the Laguna Salada.
  - (3) Mr. Francis G. French, Sarita, Texas, for the Kenedy Ranch part.

Geographic names. The name LAS PUERTAS applies to a new artesian well located at approximate latitude 27 degrees 19.8 minutes, longitude 97 degrees 38.1 minutes, and is recommended for charting.

No discrepancies were noted in charted names.

56. Commissioner precinct lines. -- An extensive investigation of the Commissioner Precinct lines was made. No marked corners could be found. However, the lines were transferred from a map in the office of Mr. C. G. Patterson, Kleberg County Surveyor, and verified by local information. No conflict was encountered and it is believed the lines as shown on the Field Edit Sheet are reasonably accurate.

Respectfully submitted, 14 February 1952

William H. Shearouse, Cartographer

William H. Shearause

Form 567 April 1945

## DEPARTMENT OF COMPUTATION

U. S. COAST AND GEODETIC SURVEY

# MONIELOATING ALDEGOR L'ANDMARKS FOR CHARTS

STRIKE OUT ONE TO BE CHARTED

Brownsville, Texas

500 14 October

I recommend that the following objects which have the following objects which have them shows the following objects which have the f charted on (MANGRACHEM) the charts indicated.

The positions given have been checked after listing by \_

							-	George	George E. Morri		
STATE MITTE	Č in				POSITION			METHOD		THA	LWV HO
Va I			LATI	LATITUDE	LON	LONGITUDE		LOCATION	DATE	98 CH	CHARTS
CHARTING	DESCRIPTION	SIGNAL	-	D.M.METERS	0	D. P. METERS	DATUM	SURVEY No.	LOCATION		OFFSI
BARN	East gable, red wood with metal top (26 ft. above	We.	27 18	1609	17 16	872	N.A. 1	Rad Plot T-9195	1949	- 1	We of 1286
	MSL,) chart outline					-	•		:		
TANK Elev)	Mood (32 ft. high, top 58 ft.above MSL).	(3)	27 17	759.3	07 46	19.5	E	Triang.	. 1939	M	£
BUILDING	(36 ft. above ground, top 57 ft.	(2)	27 17	557.7	97 39	1645.7	8	2	1912	M	
İ											
	(1) BUENA VISTA HOPEL KATER TANK 1939	EL NATER	TANK 195	39							
-	(2) BUENA VISTA HUTEL SOUTH	TEL SOUTH	CHIMNEY 1912	r 1912							
· 		•									
		J			268	8-1sc					
						/					
	j		• •	:			!				
					,						•
							-				21
								-		-	

aids to navigation, if redetermined, shall be reported on this form. The data should be considered for the charts of the area and not by individual field survey sheets. Information under each column heading should be given. Positions of charted landmarks and nonfloating This form shall be prepared in accordance with Hydrographic Manual, pages 800 to 804.

U. IL COVERGRES PRINTING OFFICE: 1949 O - 853418

### REVIEW REPORT T-9195 Topographic Map 23 May 1952

62. Comparison with Registered Topographic Surveys:

T-1624

1:20,000

1881

T-9195 supersedes this survey for nautical charting purposes.

For a discussion of the special treatment of shoreline interpretation and delineation by this survey as compared to the above survey, see item 66 below.

Minor shoreline erosion is in evidence from a comparison with this survey.

- 63. Comparison with Maps of Other Agencies:

  Sarita, Tex. (U.S.E.) 1:125,000 1909 Revised 1928

  No significant differencies are to be noted.
- 64. Comparison with Contemporary Hydrographic Surveys:
  None.
- 65. Comparison with Nautical Charts:

Chart 1117 1:460,732 5 Edition (1941) 52-1/17.

See Item 66 below for a discussion of the special treatment of shoreline interpretation and delineation in this area.

- 66. Shoreline Interpretation and delineation: Water stages in this area vary widely with meteorological conditions. The high-water line has been omitted where it is indefinite and is not marked by visible evidence on the ground. The broken line indicates the approximate inshore limits of areas subject to inundation. The dotted line represents the approximate low-water line.

  See Review Report T 9/92
- 67. Adequacy of Manuscript: This topographic map complies with Bureau standards, project instructions and with National Map Accuracy Standards.

Reviewed by:

Gordon B. Willey

T-9195 Page 2

Approved:

Chief, Review Settion # Division of Photogrammetry

Chief, Nautical Chart Branch Division of Charts

### NAUTICAL CHARTS BRANCH

### SURVEY NO. 7. 9/95

### Record of Application to Charts

DATĖ	CHART	CARTOGRAPHER	REMARKS
11/51	1117	Pisegani	Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			· · · · · · · · · · · · · · · · · · ·
			•

A basic hydrographic or topographic survey supersedes all information of like nature on the uncorrected chart. Give reasons for deviations, if any, from recommendations made under "Comparison with Charts" in the Review.

M-2168-1