

4292

Form 504

DEPARTMENT OF COMMERCE

U. S. COAST AND GEODETIC SURVEY

E. Lester Jones *Director*

DESCRIPTIVE REPORT
to accompany
Topographic Sheet # B, Nawiliwili Bay, Kauai Island T.H.

Clem L. Garner, Chief of Party

Director's instructions dated Nov. 23, 1926.

LIMITS:

This sheet includes a detailed survey of the shore-line of Nawiliwili Bay from Kawai Pt. to Kamilo. Form lines, roads, and buildings are included to approximately $\frac{1}{4}$ mile back from the coast.

GENERAL DESCRIPTION:

The shore-line of Nawiliwili Bay is composed of rocky bluffs except for the sand beach at the mouth of the Huleia River and from the dock to a point about 340 meters north of Kukii Pt. On the south side of the bay and south of the Huleia River the ground is high and rugged. On the north side of the bay the land back from the shore is mostly flat or gently sloping and is covered with sugar cane fields.

The breakwater extending from the south shore of the bay toward Kukii Pt. is about 10 feet high and is completed. The retaining wall extending out from the west shore is still under construction, being about one-half completed. A blueprint showing the proposed location of the retaining wall accompanies this sheet.


SURVEY METHODS:

The triangulation stations shown furnished control for this work and the survey was accomplished by the usual plane-table methods. Positions were found mostly by three point fix and re-sections. A traverse was run between Ninini Pt. light and Kukii Pt. light with a closing error of 3 meters which was adjusted. A closed traverse was run up the road west of Nawiliwili checking the final position by a three point fix. A spur traverse was run up the Huleia River.


Form lines were obtained as far back as the bluff line.

List of plane-table positions and statistics accompany this report.

Respectfully submitted,


Topographer

Approved and forwarded,


Chief of Party

LIST of PLANE-TABLE POSITIONS

Object	Latitude		D.M.	Longitude		D.P.	Height	Remarks
Pole	21 ⁰	56'	1621	159 ⁰	21'	212	62	White Pole
Tank	21	56	1676	159	21	335		Lower one of two black tanks
Black	21	56	1587	159	21	1064		Black tank
Der	21	56	1728	159	21	1438		Derrick at head of bay
Brown	21	57	646	159	21	998		North gable of brown house
Dock	21	57	1147	159	21	494		Loading derrick on dock
West	21	57	1251	159	21	190		West white pillar of house
Derrick	21	57	842	159	21	68		

Statute miles of shoreline 9.0

Statute miles of roads and railroads 6.5

POST-OFFICE ADDRESS: 202 Burke Bldg., Seattle, Washington.

TELEGRAPH ADDRESS:

EXPRESS OFFICE:

NOV. 26 9 01 AM '28

14 HLB
11

DEPARTMENT OF COMMERCE

U. S. COAST AND GEODETIC SURVEY

Ship SURVEYOR

November 19, 1928.

To: The Director,
U. S. Coast and Geodetic Survey.

Through: Commanding Officer, Ship SURVEYOR,
Inspector, Seattle Field Station.

From: J. C. Partington, Jr. H. & G. E.
U. S. Coast and Geodetic Survey.

Subject: Discrepancies on topographic sheets.

In reply to your letter of November 15, 1928, reference
10 HC C, I wish to state the following:

On the survey of topographic sheet No. 4292 Nawiliwili
Bay, Kauai Island T. H., scale 1:5000, the survey methods were as
follows: The plane table was set up at Ninini Point lighthouse
and a traverse run to topographic signal Last.

Signal Last was located by a rod reading taken from the
topographic signal between Ninini Point lighthouse and signal Last.
This traverse could not be closed since there is no triangulation
station on the sheet north of Ninini Point lighthouse and the trees
inshore from signal Last obscured any triangulation station which
could be used for resection.

On topographic sheet No. 4296 a traverse was run from
Ninini Point lighthouse to a triangulation station north of topo-
graphic signal Last and signal Last was located as the traverse
proceeded.

The position of signal Last as found on topographic sheet
No. 4296 is probably correct and the discrepancy on sheet No. 4292
is no doubt due to an erroneous rod reading taken from a plane table
set up at the topographic signal between Ninini Point lighthouse
and signal Last.

The position of the adjusted shore line is shown on the tracing in red and the tracing returned herewith.

No comparision of the two sheets was made in the field in order to discover discrepancies between the two. In the future this will be closely watched by me.

J. C. Partington
J. C. Partington
Jr. H. & G. E.

Forwarded
A. R. Lubbers
County St. Surveyor.

shoreline from Topo 4292
 Nawiliwili Bay, Kauai, Island

Scale: 1:5000



DEPARTMENT OF COMMERCE
U. S. COAST AND GEODETIC SURVEY

TOPOGRAPHIC TITLE SHEET

The finished Topographic Sheet is to be accompanied by the following title sheet, filled in as completely as possible, when the sheet is forwarded to the Office.

U. S. Coast and Geodetic Survey.

Register No. ^B 4292

4292

State . . . Hawaiian Is.

General locality . . . Kauai Island

Locality Nawiliwili Bay

Chief of party . . . Clem L. Garner

Surveyed by . . . J. C. Partington

Date of survey . . . January and February 1927

Scale 1 : 5000

Heights in feet above . . . Mean high water

Contour interval . . . 20 . feet.

Inked by . J.C. Partington Lettered by . J.C. Partington

Records accompanying sheet (check those forwarded): Photographs,

Descriptive report, Horizontal angle books, Field computations,

Data from other sources affecting sheet

Remarks: