

DESCRIPTIVE REPORT to accompany

TOPOGRAPHIC SHEET No. "E", Anahola Bay, Kauai Island, T.H.

F.G.Engle Chief of Party

Directors Instructions dated Nov. 23, 1926

EXTENT:

This sheet includes the shore-line of Anahola Bay, extending from about 1 mile south to 1 mile north of the bay. It also includes the topography to approximately 2 mile back from the coast.

GENERAL DESCRIPTION:

Anahola Bay situated on the north-east coast of Kauai Island is a small open bay about ½ mile across. South of Kahala Pt. the shoreline is low and strewn with bowlders. The land slopes gently back from the coast to the flat cane fields. The inner part of the bay from Kahala Pt. to Kuaehu Pt. is a sandy beach with a few scattered houses. From Kuaehu Pt. to the northern limit of the sheet the shore-line is mostly sandy with a few patches of black rocks. The land back of this section is devoted to the cultivation of pine-apples.

The Anahola River empties into this bay and is navigable by row-boats for about 1 mile where rocks and rapids impede further progress. The mouth of the river is obstructed by a sand bar which limits the depth to from 1 to 2 feet at time of low water. Rice is grown in this valley.

Breakers extend off the east coast from the south limit of the sheet to the inside of Kahala Pt. to a distance of 100 to 200 meters. A reef partly bare at time of extreme low water makes out about 350 meters off the coast from Kuaehu Pt. to latitude 22° 10°.

On account of exposure to the northeast trade winds this bay is usually rough and has no commercial importance.

LANDMARKS and AIDS TO NAVIGATION:

The most important landmark in this vicinity is the pinnacle Pun Kononae 1430 feet above mean high water. This pinnacle rises almost vertically from the surrounding ground and is easily distinguished from seaward. It is about 1 miles back from the coast.

Kahaka Pt. light marks the south side of Anahola Bay and the entrance is marked by 2 white unlighted range beacons about 16 feet high. At the inner part of the bay is an abandoned dock, the concrete piles of which still remain.

SURVEY METHODS:

į

The 6 triangulation stations shown, including Kahala Pt. light, furnished control for this work. This work was accomplished by the usual plane-table methods and all traverses closed within the required limits. The limits of breakers and the reef mentioned above were sketched in by a hydrographic party.

LIST of PLANE-TABLE POSITIONS

•	Name	Lati	tude	D.M. meters	Longi tude		D.P. meters	Remarks	
	FLAG	22 ⁰ (081	1449	159 ⁰	18'	394	Flag in 1 inch pipe projecting 1 foot.	
	FRONT		08	1571	159	18	823	Front range beacon	
	REAR	22 . (08	1437	159	18	868	Rear range beacon	

Statute miles	Οſ	shore-line		5.2
Statute miles	of	rivers	ads	1.0
Statute miles	of	roads and railro	ads	5.5

Respectfully submitted,

Approved and forwarded,

Chief of Farty

7

Topographer

Inspected January, 1928 and Jourd adoquate.

E. Eleis

DEPARTMENT OF COMMERCE

U. S. COAST AND GEODETIC SURVEY

TOPOGRAPHIC TITLE SHEET

The finished Topographic Sheet is to be accompanied by the following title sheet, filled in as completely as possible, when the sheet is forwarded to the Office.

U. S. Coast and Geodetic Survey.

Register No. 4299

State Hawalian Islands
General locality Kauai Tsland
Locality Anahola Bay
Chief of party F.G. Engle
Surveyed by J.C. Partington
Date of survey April 1927
Scale 1 : 5,000
Heights in feet above Mean high water
com line Contour interval . 20 feet.
Inked by .J.C.Partington Lettered by J.C.Partington
Records accompanying sheet (check those forwarded): Photographs,
Descriptive report, Horizontal angle books, Field computations,
Data from other sources affecting sheet
•

Remarks: