9160



Diag. Cht. No. 1229

U. S. COAST AND GEODETIC SURVEY

DEPARTMENT OF COMMERCE

DESCRIPTIVE REPORT

Type of Survey Topographic Field No. Ph-45 (49) Office No. T-9160 LOCALITY State North Carolina General locality Roanoke Sound Locality Nags Head 194 53 CHIEF OF PARTY Harry F. Garber, Chief of Field Party Arthur L. Wardwell, Tampa Photogrammetric

LIBRARY & ARCHIVES

DATE September 28, 1955

B-1870-1 (I)

DATA RECORD

T-9160

Project No. (II): Ph-45 (49)

Quadrangle Name (IV):

Field Office (II): Manteo, N.C.

Chief of Party: Harry F. Garber

Photogrammetric Office (III): Tampa, Florida

Officer-in-Charge: Arthur L. Wardwell

Instructions dated (II) (III): 15 September 1949 Copy filed in Division 19 January 1950 (Supplement One) Photogrammetry (IV)

Copy filed in Division of

Office Files

Method of Compilation (III): Graphic

Manuscript Scale (III): 1:20,000

Stereoscopic Plotting Instrument Scale (III): Inapplicable

Scale Factor (III): None

Date received in Washington Office (IV): EB 2 7 195/Date reported to Nautical Chart Branch (IV):

Applied to Chart No.

Date:

Date registered (IV): SEP 8 1955

Publication Scale (IV):

Publication date (IV):

Geographic Datum (III):

N. A. 1927

Vertical Datum (III): MSL

Mean sea level except as follows: Elevations shown as (25) refer to mean high water Elevations shown as (5) refer to sounding datum i.e., mean low water or mean lower low water

Reference Station (III): BODIE ISLAND NORTH BASE, 1849

35°53° 56"932 (1754.7 m) Long.: 75°35° 52"613 (1319.4 m)

Plane Coordinates (IV):

State:

Zone:


Y=

X=

Roman numerals indicate whether the item is to be entered by (II) Field Party, (III) Photogrammetric Office, or (IV) Washington Office.

When entering names of personnel on this record give the surname and initials, not initials only.

Adjusted knowiestestx



Areas contoured by various personnel (Show name within area) (II) (III)

DATA RECORD

Field Inspection by (II): Ralph G Holland Topographic Engr. Date: MAR-APR., 1950

Planetable contouring by (II): Richard E. Conway Jr.

Date: August, 1950

Cartographic Survey Aid

R.L. Me Glinchey Completion Surveys by (II):

Date: March 1953

Mean High Water Location (III) (State date and method of location):

Air Photo Compilation

15 May, 1950.

(W.O.) Projection and Grids ruled by (IV): S. R.

Date: 20 October 1950

Projection and Grids checked by (IV): H. D.W. (W.O.)

25 October 1950

Control plotted by (III): I. I. Saperstein

Date: 8 December 1950

Control checked by (III): R. R. Wagner Date: 15 December 1950

Radial Plot XXX Stexeoscopic

Cockreckerston by (III): M. M. Slavney

Stereoscopic Instrument compilation (III):

Date:

15 January 1951

Planimetry

Inapplicable

Date:

Contours

Date:

C. J. Downing Manuscript delineated by (III):

Date: 19 March 1951

Photogrammetric Office Review by (III): J. A. Giles

March 1951

Elevations on Manuscript

checked by (the (III):

C. J. Downing

Date:

16 March 1951

Camera (kind or source) (III):

Stagle Mark Zamerax ox 200 Zx Easx Extenseth
Fairchild Cartographic - 6" Metrogon lens, Camera "0"

		PHOTOGRAPHS (III		
Number	Date	Time	Scale	Stage of Tide
1798	5-12-49	13:42	1:20,000	0.1 ft. above M.L.W.
1799	5-12-49	13:42	n	II
1800	5-12-49	13:43	ii ii	ii.
1801	5-12-49	13:43	11	ii ii
1802	5-12-49	13:44	Ų.	ú

Tide (III)

Reference Station: HAMPTON ROADS, VA
Subordinate Station: OREGON INLET. N.C.

Subordinate Station:

Washington Office Review by (IV): Everett H. Ramey

Final Drafting by (IV): Pat Lach

Drafting verified for reproduction by (IV):

Proof Edit by (IV):

Land Area (Sq. Statute Miles) (III):

Shoreline (More than 200 meters to opposite shore) (III): 22 miles
Shoreline (Less than 200 meters to opposite shore) (III): 2.3 miles

Control Leveling - Miles (II): 5 miles of third order, 4 miles of fly levels. Total 9 miles

Number of Triangulation Stations searched for (II): 3 Recovered: 1 Identified: 1

Number of Triangulation Stations searched for (II): 3 Recovered: 1
Number of BMs searched for (II): 16 Recovered: 4

Number of Recoverable Photo Stations established (III): 8
Number of Temporary Photo Hydro Stations established (III)None

Remarks:

 Ratio of Ranges
 Mean Range
 Spring Range

 1.0
 2.5
 3.0

 0.7
 1.8
 2.2

Date: 5 Feb 1954

Date: 6-1-55

Date:


Date:

Identified:

3

TOPOGRAPHIC MAPPING PROJECT PH-45 (49)

NORTH CAROLINA, Vicinity of Albemarle Sound



`

`

Map T-9160 is one of eighteen topographic maps in Project Ph-45(49). It covers land area southward of Nags Head, North Carolina between the Atlantic Ocean and the Roanoke Sound.

Project Ph-45(49) is a graphic compilation project. Field work in advance of compilation included the establishment of additional horizontal and vertical control, the delineation of contours directly on the photographs by planetable methods, field inspection of all features and the investigation of geographic names and political boundaries.

Map T-9160 was compiled at a scale of 1:20,000 using single-lens photographs taken in 1949. The map was then field edited. After the addition of hydrographic data, the map will be forwarded to the Geological Survey for publication as a standard 7½' topographic map.

Items registered under T-9160 will include a descriptive report, a lithographic copy of the map manuscript at a scale of 1:20,000 and a color copy of the published map at a scale of 1:24,000.

Preliminary Report

FIELD INSPECTION REPORT QUADRANGLE T-9160 Project Ph-45 (49)

Harry F. Garber, Chief of Party

The field work for this quadrangle was done in compliance with the Director's Instructions, Project Ph-45 (49) dated 15 September 1949 and Supplement One instructions dated 19 January 1950. In addition to contouring as indicated on Page 2, the field work was accomplished by:

Name and Title

Phase

Date

Ralph G. Holland Topographic Engr. Horizontal & Vertical March, 1950 to Control Recovery & Identification. April, 1950 Interior Inspection, Shoreline, Fly levels, and 3rd order levels. Supplemental horizontal control.

AREAL

2. AERIAL FIELD INSPECTION

This quadrangle lies in Dare County, North Carolina covering an area of land known as Bodie Island located between the Atlantic Ocean and Roanoke Sound and in addition some large marsh islets in Roanoke Sound

The only town or settlement in this quadrangle is the unincorporated town of Nags Head which is principally a summer resort site consisting of small hotels, tourists cabins, beach cottages and a few business houses. Practally everything is closed during the winter season except for a few business houses that remain open during hunting season.

The area is served by one primary highway, U.S. Highway 158 which parallels the Atlantic shore. The road leading south to Oregon Inlet is paved for about one mile from its juncture with U.S. Highway 158 and the remainder is a sand road served from the south by a ferry.

There are no railroads within this area.

The land area consists chiefly of shifting sand hills except for some low marsh area along the shores of Roanoke Sound.

See 356

The quality of the photographs is satisfactory. No difficulty should be encountered in interpretation of tones by the compiler.

The field inspectin is believed to be complete.

3. HORIZONTAL CONTROL

- (a) A third order position of Control Pt. "B" was determined by a three point fix to supplement the horizontal control.

 **X Station unmonumented. Used for controlling photogrammetric plot.
 - (b) No datum adjustments were made by the field party.
 - (c) No stations other than the USC&GS were recovered. Does any exist?
 - (d) Lost station is the NAGS HEAD C.G. STATION, 1933
- (e) All Coast & Geodetic stations were searched for and reported on Form 526.

4. VERTICAL CONTROL

In order to supplement the existing vertical control, a third order line was run along U.S. Highway 158 from the southwestern limits of quadrangle northward to the Nags Head Coast Guard station. A spur of this third order level line was run for about one mile south along the Oregon Inlet Road from its junction with U.S. Highway 158.

(a) Bench Marks

(1) Third Order USC&GS

M-249, 1949

N-249, 1949

P-249, 1950

M 14.5 (USGS) 1939

M 13.5 (USGS) 1939

(All of the above Bench Marks were established by third order leveling by the field party)

(2) Other Agencies (Third order Bench Marks)

M 10 (USGS) Not Recovered

M 10.5 (USGS) Not Recovered

M 11.0 (USGS) Not Recovered

M 11.5 (USGS) Not Recovered

M 12.0 (USGS) Destroyed

M 12.5 (USGS) Recovered

M 13.0 (USGS) Recovered

M 13.5 (USGS) Recovered

M 14.0 (USGS) Not Recovered

M 14.5 (USGS) Recovered

M 17.5 (USGS) Recovered

784 71 (USGS) Destroyed

- (3) Two USGS Bench Marks, namely 13.5 and 14.5 were tied into the tird order level line by this party which proved a datum difference of 0.320 feet. This datum difference was applied to all USGS Bench Marks that were used. The level line was adjusted to USGS Bench Marks Number 13.5 and 14.5 by the Washington Office.
- See \$ 67
- (b) Four miles of fly levels were run to establish supplemental vertical control for contouring and closed on third order bench marks.
 - (c) The first and last level points are: 60-01 to 60-08.

5. CONTOURS AND DRAINAGE

All contouring was done by planetable methods directly on single lens photographs at a five foot interval. In some cases the peaks run higher than the last contour shown. This is because they are so small and sharp and could not be delineated accurately on 1:20000 scale. Such points are sindicated on the photographs. In the northern portion of the Quad and on the sound side are concentrated most of the higher dunes. A five foot interval was maintained here up to their summit.

The drainage pattern, although very indefinite and irregular is generally toward the sound. Water stands in pockets between the two ridges that parallel the ocean and sound. Because of the ridge parallel to the ocean, there is practically no drainage in this direction.

6. WOODLAND COVER

There is no woodland coverage in the quadrangle.

7. SHORELINE AND ALONGSHORE FEATURES

- (a) The mean high water line along the Atlantic Shore was indicated on the photographs by both field inspection and reference measurements. The shoreline is generally apparent along the sound side.
- (b) The low water line was not indicated on the photographs along the barrier beach since the photography was made near the time of mean low water. On the sound side there is practically no perceptible periodic tide change and the mean low water line and the mean high water line are synonymous.
 - (c) The foreshore is sand.
 - (d) Inapplicable.
- (e) Docks, wharves, piers and landings are clearly discernible on the photographs and clearly labeled.

8. OFFSHORE FEATURES

There are no offshore features that require further investigation.

9. LANDMARKS AND AIDS

(a) Landmarks and non-floating aids to navigation are listed on Form 567.

There are no aeronautical aids within the quadrangle.

10. BOUNDARIES, MONUMENTS AND LINES

For legal descriptions of all boundaries in this project, see "Special Boundry Report" which has been submitted by Mr. R.L.

McGlinchey. * Filed under project data in Div. of Photogrammetry.

11. OTHER CONTROL

Recoverable topographic stations established are:

ADAM, 1950
ARTO, 1950

AXER, 1950

BAND, 1950

BANK, 1950

CFalls on T-9159

BOUNDARY MK-1 (Nags Head C.G. Station) 1950

DANA, 1950

GABLE

SPIRE, 1950

TOWER, 1950

CHIMNEY, 1950

12. OTHER INTERIOR FEATURES

All roads and buildings were classified in accordance with instructions.

The only bridge over navigable waters in the area is the swing draw bridge on U.S. Highway 158 which crosses Roanoke Sound in the southwestern section of the quadrangle. A new bridge is at present under construction near this site to be used in lieu of this bridge. There will be some revision in the location of the highway approaches to this bridge. This new bridge and revision in the highway approaches to the bridge should be checked by the field editor.

Clearances were obtained on the above bridge and on one fixed bridge located on U.S. Highway 158 crossing Roanoke Sound between two islands just east of the swing draw bridge.

All bridge data is shown on photographs.

There is one overhead transmission line crossing navigable waters in the quadrangle. This line crosses Roanoke Sound paralleling the south side of the swing draw bridge and clearance was obtained and clearly noted on the photograph. Check Bridge Book for discrepancies in clearance bridges

There are no airports, landing strips, or submarine cables in this quadrangle.

13. GEOGRAPHIC NAMES

This special report will be submitted by Mr. R.L. McGlinchey
This report is filed in the Geographic Names Sect., Div. of Charts.

14. SPECIAL REPORT AND SUPPLEMENTAL DATA

Except for items 10 and 13 above, there are no special data for this sheet.

2 June 1950 Submitted by:

For Harry F. Sale Ralph G. Holland Topographic Engr.

>-
5
4
Ε
ē
5
50
þ0
9
5
Ē
a.

	-							
STATION	SOURCE OF IN FORMATION (INDEX)	ратим	LATITUDE OR V-COORDINATE LONGITUDE OR x-COORDINATE	-COORDINATE	DISTANCE FROM GRID IN FEET, OR PROJECTION LINE IN METERS FORWARD (BACK)	DATUM	N.A. 1927 - DATUM DISTANCE FROM GRID OR PROJECTION LINE IN METERS FORWARD (BACK)	FACTOR DISTANCE ECTION LINE FROM GRID OR PROJECTION LINE IN METERS (BACK) FORWARD (BACK)
BODIE ISLAND	S.P.	N.A.	35 53	56.932			1,754.7 (9	94.5)
NORTH BASE, 1849	21.8	1927	75 35	52,613				185.3)
		I						
		I——						
		L_,						
] 						
		·					•	
		. <u></u> ł .						
								W. 2388
COMPUTED BY.	Dawsey		17 August 1950	st 1950	CHECKEN BY. I.I.Saperstein)aperstefi	4 4	6 Dec. 1950

COMPILATION REPORT T-9160

PHOTOGRAMMETRIC PLOT REPORT.

This report will be submitted with T-9159.

31. DELINEATION.

Compiled by graphic methods. No unusual methods were used.

32. CONTROL.

Horizontal control was adequate. Identification, placement and density were satisfactory.

33. SUPPLEMENTAL DATA.

None used.

Sec \$4

34. CONTOURS AND DRAINAGE.

No difficulty was encountered in the delineation of contours See \$56 or drainage.

35. SHORELINE AND ALONGSHORE DETAILS.

Shoreline inspection was adequate. Low-water line was delineated from the photographs since photography was done at low tide. Reference Item 7(b).

36. OFFSHORE DETAILS.

No unusual problems were encountered while delineating offshore detail.

37. LANDMARKS AND AIDS.

No unusual methods employed. See §65

38. CONTROL FOR FUTURE SURVEYS.

Eight (8) topographic stations are being submitted on Form 524.

These topographic stations have been listed under Item 49.

39. JUNCTIONS.

Adjoining quadrangles were not completed at this time.

See \$58

40. HORIZONTAL AND VERTICAL ACCURACY.

No statement is required.

See \$53

46. COMPARISON WITH EXISTING MAPS.

Comparison was made with U. S.C. of E. quadrangle ROANOKE See \$62.4 \$43 ISLAND, scale 1:125,000, dated 1942.

47. COMPARISON WITH NAUTICAL CHARTS.

Comparison was made with NAUTICAL CHART, 1229, scale 1:80,000, dated December 1942, corrected to August 7, 1950.

ITEMS TO BE APPLIED TO NAUTICAL CHARTS IMMEDIATELY.

None

ITEMS TO BE CARRIED FORWARD.

None.

Charles J. Downing Photogrammetric Aid

Approved and Forwarded:

Arthur L. Wardwell Chief of Party

49. NOTES FOR THE HYDROGRAPHER.

A list of eight (8) recoverable topographic stations which may be useful to the hydrographer follows:

ADAM ARTO AXER BAND BOUNDARY Mon. #15 SHACK GABLE ENTE SPIRE TOWER	- 1 - 1 - 1	1950 1950 1950 1950 1950 1950	Reported 1953 as destroyed. EHE
CHIMNEY		950	

51. METHODS

The field edit of this quadrangle was accomplished by traversing, via truck, all roads, and walking to other areas in which the reviewer requested information. The shoreline was inspected from a skiff.

Corrections and additions were made by standard surveying methods in conjunction with visual inspection.

The reviewer's questions are answered on the discrepancy print, field edit sheet, field photographs 49-0-1798, 1799, 1799A, 1801, 1802 and this report.

Deletions have been noted on the field edit sheet, and the field photographs. A legend appears on the field edit sheet which is self-explanatory.

Field work was accomplished intermittently during February, 1953.

52. ADEQUACY OF COMPILATION

The map compilation is adequate and will be complete after field edit data is applied. Complete re-classification of buildings was made on the field photographs for all areas adjacent to U.S. Highway 158 along Nags Head Beach, north of the causeway to Manteo.

53. MAP ACCURACY

Topographic station "BAND, 1950" was re-identified by the sub-station method as a check against the original identification by 3-point fix. The position of this station as delineated on the map manuscript could not be reconciled as to the shoreline and other topographic features. The horizontal accuracy of map detail in all other areas appears adequate.

A small area of isolated sand spots on Bodie Island just east of Headquarters Island was found to be above five (5) feet and contoured on field photograph 49-0-1802.

54. RECOMMENDATIONS

It is recommended that shifting sand dunes of the nature of those portrayed in the northern areas of this sheet, and outlined in red on the field edit sheet, not be contoured, but only an occasional spot elevation be shown on the higher peaks.

55. EXAMINATION OF PROOF COPY

It is believed that Mr. David Cox, Jr., registered land surveyor, Hertford, N. C., or Mr. Melvin Daniels, Dare County Registrar of Deeds, Manteo, N. C., are best qualified to examine a proof copy of this map.

A spot check of Geographic Names was made and found to be in excellent agreement with the Geographic Name List.

56. CONTOURS AND SAND DUNES

The sand dunes included in this sheet are classified in three groups:

- (a) All that area along the Barrier Beach included east of U. S. Highway 158 and east of the new road to Oregon Inlet. The sand dunes in this entire area are very similar. These dunes can be classed as more stable than shifting in that grass covers most of the sand. The dunes are not too high and are not moving steadily in one direction as in areas north of here. South of the causeway to Manteo, the 5 and 10-foot carrying contours along the beach and inland along the new road are fairly steady. North of the causeway, the five and ten-foot contour along the beach and the ten-foot contour that generally follows U.S. 158 is also fairly steady. However, the 15-foot contour and any higher elevations are very unsteady. These higher areas are dotted with hundreds of small peaks and depressions which are subject to change by varying wind directions. It is recommended that in this area, the five and ten-foot contour be mapped and that some spot elevations be shown on the larger and higher areas.
- (b) Areas immediately south and west of Nags Head, and circled in red on the Field Edit Sheet; are classed as shifting sand dunes. The contours here are recommended for deletion. These areas should be labeled "SHIFTING SAND DUNES" and only occasional spot elevations shown on the highest peaks.
- (c) All other areas where contours are shown, are classed as stable sand areas and should be mapped. These areas are under ten (10) feet in elevation, generally isolated, and usually surrounded by bushes which afford protection against the wind.

57. OTHER INTERIOR FEATURES

Since the original photography and field work, a new bridge has been built over Roanoke Sound and the old bridge removed. That portion of the new bridge falling in T-9160 has been located on the field edit sheet and a proper junction made with the field edit sheet of T-9159. For further bridge data, see field edit sheet for T-9159.

Also, a new road has been built from approximately one mile south of the causeway to Manteo, to Oregon Inlet. This road has been located on the field edit sheet and a proper junction made with T-9278.

The U. S. Department of Interior, National Park Service, is in the process of acquiring all that land south of the causeway to Manteo, to Cape Hatteras. As of this date, no permanent boundaries have been established.

58. JUNCTIONS

A satisfactory junction was made with T-9159 on the west, and T-9278 on the south. The waters of the Atlantic Ocean are on the north and east.

12 March 1953 Submitted by:

Richard J. McGlinchey, of Carto. Surv. Aid

25 March 1953 Approved by:

Paul Taylor //
Lt. Comdr., USC&GS
Chief of Party

PHOTOGRAMMETRIC OFFICE REVIEW

50.

T- 9160

1. Projection and grids J.G. 2. Title J.G. 3. Manuscript numbers J.G. 4. Manuscript size J.G.	
CONTROL STATIONS	
5. Horizontal control stations of third-order or higher accuracy M.M.S. 6. Recoverable horizontal stations of less	
than third-order accuracy (topographic stations) J.G. XXPANIAN SANIAN 8. Bench marks J.G.	
9. Plotting of sextant fixes J.G. 10. Photogrammetric plot report J.G. 11. Detail points J.G.	
ALONGSHORE AREAS	
(Nautical Chart Data)	
12. Shoreline J.G. 13. Low-water line J.G. 14. Rocks, shoals, etc. J.G. 15. Bridges J.G. 16. Aids	CX (SEX
to navigation <u>J.G.</u> 17. Landmarks <u>J.G.</u> 18. Other alongshore physical features <u>J.G.</u> 19. Other along—	
shore cultural features J.G.	
PHYSICAL FEATURES	
20. Water features J.G. 21. Natural ground cover J.G. 22. Planetable contours J.G. 23. Natural ground cover	
24. Contours in general <u>JaGa</u> 25. Spot elevations <u>JaGa</u> 26. Other physical	
features <u>J.G.</u>	
CULTURAL FEATURES 27. Roads J.G. 28. Buildings J.G. XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	
BOUNDARIES	
31. Boundary lines J.G. XXXXXXXXXXXXXXXXXX	
MISCELLANEOUS	
33. Geographic names J.G. 34. Junctions J.G. 35. Legibility of the manuscript J.G. 36. Discrepancy	
overlay J.G. 37. Descriptive Report J.G. 38. Field inspection photographs J.G. 39. Forms J.G.	
40. Jesse A. Giles Jesse Milliam A. Rasure	
Revigier Supervisor, Review Section or Unit	
41. Remarks (see attached sheet)	
FIELD COMPLETION ADDITIONS AND CORRECTIONS TO THE MANUSCRIPT	
42. Additions and corrections furnished by the field completion survey have been applied to the manuscript. The manuscript is now complete except as noted under item 43.	
Compiler Supervisor	

43. Remarks:

Review Report Topographic Map T-9160 5 February 1954

62. Comparison with Registered Topographic Surveys .-

T-351	1:20,000	1851
354	η´	1849
354 3538	1:40,000	1915-16

Differences in shoreline and cultural features exist between these surveys and T-9160. Map T-9160 is to supersede the above surveys for the area encompassed by T-9160.

63. Comparison with Maps of Other Agencies.

Roanoke Island, N.C. (USE) 1:125,000 1943

T-9160 is in general agreement with this map. Some changes in culture have occurred since this 1943 map was published.

- 64. Comparison with Contemporary Hydrographic Surveys .- None
- 65. Comparison with Nautical Charts .-

1229 1:80,000 1942 corr. to 53-8/24

Differences in shoreline and culture exist. Changes made to the map manuscript during this review are shown in red. Note the position correction made during this review to the attached Form 567 for landmark: Tower.

- 66. Adequacy of Results and Future Surveys. This map meets the "ational Standards of Map Accuracy and complies with project instructions.
- 67. Vertical Control. Reference par. (a) (3), sub-heading 4. The adjustment of this level circuit in conjunction with the adjustment of two other level circuits which were also referenced to BM M-14.5 (USGS) was made by the Section of Leveling, Div. of Geodesy. It was concluded from this investigation that the elevation of BM M-145, as published, should be retained. The elevations of benchmarks established in conjunction with this survey were accordingly recomputed by the Section of Leveling.

The application by the contouring party of a datum difference to the USGS benchmarks on Bodie Island is in error. However, the error is insignificant in securing the accuracy of contours.

68. Bridges and cables: The fixed bridge appearing on this map is not listed in the USE bridge book.

69. Contours and Sand Dunes: Reference par. (a) Sub-heading 56. Parts of the area referred to required further generalization to permit symbolization and contouring. The selection of the limits between the stable and shifting dunes is difficult and somewhat arbitrary.

Reviewed by:

APPROVED

Chief, Review Branch Div. of Photogrammetry

Chief, Nautical Chart Branch Division of Charts

Div. of Photogrammetry nuk

PHOTOGRAMMETRIC REVIEW SECTION

DEPARTME TOF COMMERCE

U. S. COAST AND GEODETIC SURVEY

NONFLOATING AIDS OR LANDMARKS FOR CHARTS

TO BE CHARTED TO BE DELETED

STRIKE OUT ONE

The positions given have been checked after listing by

charted on (Aeleted from) the charts indicated.

Tampa Photogrammetric Office

I recommend that the following objects which have Mare not been inspected from seaward to determine their value as landmarks be

Charles J. Downing

Arthur L. Mardwell

тядно	CHARTS	9	1229								17
ТЯАНЭ	OBE		×	W N							
TAA		Z									
	DATE	LOCATION	05/6/5	=							
METHOD	LOCATION	SURVEY No.	Red. Flo	=		M					
		DATUM	M.A. 1927	=		Ship					
*	LONGITUDE	D. P. METERS	705	619		Chaunel					
POSITION *	LONG	- 0	75 37	75 37	2 Mrs	Roznoke Sound Channe.					
	LATITUDE	D. M. METERS	1655	958	1953.	odnoke					
	LATIN	-	35 52	35 52	. 7	23					
		SIGNAL			blanetabl	these to					
NORTH CAROLINA		DESCRIPTION **	ROANOKE ISLAND, Red box on pile	ROANOKE ESLAND Black square daybeacon on pile	* Positions were verified by blanetable	** 1953 Light List designates					
STATE		CHARTING	Lt. 26	Bn. 23							

This form shall be prepared in accordance with Hydrographic Manual, pages 800 to 804. Positions of charted landmarks and nonfloating aids to navigation, if redetermined, shall be reported on this form. The data should be considered for the charts of the area and not by Jim I I L wiyon

April 1945 .HOTOGRAMMETRIC REVIEW SECTION

T OF COMMERCE DEPARTME

U. S. COAST AND GEODETIC SURVEY

NONFLOATING AIDS OR LANDMARKS FOR CHARTS

TUO :	
STRIKE	
ED	8
CHARTE	H
HA	山山
U	OX
BE	4
10	100

ONE

Tampa Photogrammetric Office

19 51

28 February

I recommend that the following objects which have made not been inspected from seaward to determine their value as landmarks be charted on (deletal from) the charts indicated.

Charles J. Downing The positions given have been checked after listing by

Chief of Party. Arthur L. Merdwell

ROOF STATE OF STATE O	CTATE					POSITION			METHOD		THAH	
Boof finish of 100 loud, Hage Head 35 55 1790 75 36 1006 1927 1-9160 5/9/50 X	31416	NORTH CANOLINA		LAT	TTUDE	LONG	SITUDE		LOCATION	DATE	OBE C	
Boof finial of lookout, Hage Head 35 55 1790 75 36 1006 1927 T-9160 5/9/90 x 122	CHARTING		SIGNAL	1	D. M. METERS		D. P. METERS		SURVEY No.	LOCATION	HSNI	
Roof finital of lookout, Nage Need 35 55 1799 75 36 1000 1841. Rad. Plot x 122 0.G. Statton, ht = 48 (55) 7 195 1799 75 36 1000 1987 7-9160 5/9/50 x 122 1799 1987 1987 1987 1987 1987 1987 1987								yek.				-10
	TOWER	Roof finish of lookout, Nags Head G.G. Station, ht = 48 (55)			4	mayek 75 36	900E		Rad. Plos T-9160	5/9/50	×	1229
						7						
												*
							**					6
		•										
18				files:								
												18

This form shall be prepared in accordance with Hydrographic Manual, pages 800 to 804. Positions of charted landmarks and nonfloating aids to navigation, if redetermined, shall be reported on this form. The data should be considered for the charts of the area and not by

48. GEOGRAPHIC NAME LIST.

Investigation incomplete at this time - Geographic Names will be listed after Field Edit.

Those names shown on the map manuscript are for the most part taken from the Nautical Chart and are indisputable.

North Carolina -- Dare County -· Atlantic Ocean ~ · Bodie Island · Roanoke Sound . 'U.S. No. 158

Bells Island V · Headquarters Island V ' Rockhall C,eek · House Island · Grun Island · Pond Island · Little Bridge Jeanettes Ocean Pier · Cedar Island · Big Penguin Island · Little Penguin Island ' Nags Head Island . St. Andrews by the Sea Church V · Nags Head V

Mags Head Coast Guard Station No Try

Roans Ishad Project Names Report, before

Field Edit.

5-8-52 L. HECK

Hydrography was added to the map manuscript in accordance with the general specifications of 18 May 1949.

Depth curves and soundings are in feet at mean low water datum and originate with the following C&GS hydrographic surveys:

H-257	1:20,000	1851
1053	1:40,000	1870
3772	1:20,000	1915

Also two shoels were added in accordance with Nautical Chart 1229, 1:80,000, 1942 corrected to 53-8/24. These were reported shoels and have not been surveyed by C&GS. Comparison of other hydrography was made with this chart.

Hydrography was compiled by Everett H. Ramey on 3 March 1954 and verified by O. Svendsen on 11 March 1954.

Everett H. Ramev

NAUTICAL CHARTS BRANCH

SURVEY NO. 9160

Record of Application to Charts

DATE	CHART	CARTOGRAPHER	REMARKS
10-28-54	1229	c.wilson	Before Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			Before After Verification and Review
			· · · · · · · · · · · · · · · · · · ·
			·

M-2168-

A basic hydrographic or topographic survey supersedes all information of like nature on the uncorrected chart. Give reasons for deviations, if any, from recommendations made under "Comparison with Charts" in the Review.